

PIÈCES DE RACCORDEMENT À BRIDES

Bride de réduction, contre-bride d'étanchéité

CARACTÉRISTIQUES :

- Revêtement époxy bleu 250 microns.
- Matière fonte EN-GJS500/7.

Bride de réduction double goujonnage (R-230)



Référence	DN	Nombre de trou	PN	Poids kg
RES_230000	60x40	4-4	10-16	5,070
RES_230002	60x50	4-4	10-16	5,260
RES_230004	65x40	4-4	10-16	5,520
RES_230006	65x50	4-4	10-16	5,540
RES_230008	80x40	8-4	10-16	5,580
RES_230010	80x50	8-4	10-16	5,850
RES_230012	80x60	8-4	10-16	6,025
RES_230014	80x65	8-4	10-16	6,065
RES_230016	100x40	8-4	10-16	6,600
RES_230017	100x50	8-4	10-16	6,300
RES_230018	100x60	8-4	10-16	7,800
RES_230020	100x65	8-4	10-16	7,900
RES_230022	100x80	8-8	10-16	6,900
RES_230024	125x60	8-4	10-16	8,200
RES_230026	125x65	8-4	10-16	8,300
RES_230028	125x80	8-4	10-16	8,735
RES_230030	125x100	8-8	10-16	9,030
RES_230032	150x100	8-8	10-16	11,200
RES_230042	200x150	12-8	10	16,600
RES_230046	250x200	12-12	10	21,600
RES_230048	300x200	12-12	10	27,730
RES_230050	300x250	12-12	10	28,000

CONTRE-BRIDE D'ÉTANCHÉITÉ (R-290)

- Pour tuyau en fonte joint coulé plomb.
- Revêtement époxy bleu 250 microns.



Référence	DN	PN	Poids kg
RES_290000	50	16	4,800
RES_290002	65	16	6,180
RES_290004	80	16	7,560
RES_290006	100	16	8,650
RES_290008	125	16	10,250
RES_290010	150	16	11,500
RES_290012	175	16	12,825
RES_290014	200	16	14,150
RES_290016	250	16	19,850
RES_290018	300	16	29,050
RES_290020	350	16	32,900
RES_290022	400	16	36,750