

CLAPET TOUTES POSITIONS EN FONTE

CARACTÉRISTIQUES :

- Corps fonte revêtu époxy bleu.
- Matière fonte EN-GJS500/7.
- Joint EPDM.

(R-240)



Référence	DN	Écartement	PN	Poids kg
RES_240002	50	100	10-16	6,000
RES_240004	65	120	10-16	9,000
RES_240006	80	140	10-16	11,000
RES_240008	100	165	10-16	15,500
RES_240010	125	195	10-16	23,500
RES_240012	150	230	10-16	34,500
RES_240014	200	290	16	56,500
RES_240016	250	355	16	97,500
RES_240018	300	400	16	145,500
RES_240020	350	480	10	185,000
RES_240022	400	550	10	260,000
RES_240024	500	680	10	480,000
RES_240026	600	800	10	630,000

FILTRE EN Y À TAMIS FONTE

(avec vanne de purge) (R-245)



Référence	DN	Écartement	PN	Poids kg
RES_245002	50	230	16	8,780
RES_245004	65	290	16	11,900
RES_245006	80	310	16	15,400
RES_245008	100	350	16	22,100
RES_245010	125	400	16	31,100
RES_245012	150	480	16	44,200
RES_245014	200	600	10-16	76,300
RES_245016	250	730	10-16	115,500
RES_245018	300	850	10-16	170,000

(sans vanne de purge) (R-250)

Référence	DN	Écartement	PN	Poids kg
RES_250000	40	200	16	5,670
RES_250002	50	230	16	8,650
RES_250004	65	290	16	11,700
RES_250006	80	310	16	15,200
RES_250008	100	350	16	21,900
RES_250010	125	400	16	30,800
RES_250012	150	480	16	43,900
RES_250014	200	600	10-16	76,000
RES_250016	250	730	10-16	115,000
RES_250018	300	850	10-16	169,500



Fiche technique
du catalogue disponible
sur scop-fml.com

PN10

PN16