

COLLET, BRIDE ANTI-FLUAGE (électrosoudable)



Collet nu (I-50E)

Référence	Ø ext poly	Poids kg
ELEC_COLNU25	25	0,049
ELEC_COLNU32	32	0,065
ELEC_COLNU40	40	0,093
ELEC_COLNU50	50	0,133
ELEC_COLNU63	63	0,213
ELEC_COLNU75	75	0,340
ELEC_COLNU90	90	0,547
ELEC_COLNU110	110	0,792
ELEC_COLNU125	125	0,785
ELEC_COLNU140	140	1,380
ELEC_COLNU160	160	1,783
ELEC_COLNU180	180	2,033
ELEC_COLNU200	200	3,367
ELEC_COLNU225	225	3,483
ELEC_COLNU250	250	4,978
ELEC_COLNU280	280	5,806
ELEC_COLNU315	315	7,529
ELEC_COLNU355	355	10,750
ELEC_COLNU400	400	16,200
ELEC_COLNU450	450	27,500
ELEC_COLNU500	500	30,500
ELEC_COLNU560	560	34,160
ELEC_COLNU630	630	38,430



Bride en fonte recouverte
en polypropylène (I-51E)



Référence	Ø ext poly	DN	PN	Poids kg
ELEC_BRINU25	25	20	10-16	0,450
ELEC_BRINU32	32	25	10-16	0,500
ELEC_BRINU40	40	32	10-16	0,550
ELEC_BRINU50	50	40	10-16	0,750
ELEC_BRINU63	63	50	10-16	0,900
ELEC_BRINU75	75	65	10-16	1,100
ELEC_BRINU90	90	80	10-16	1,300
ELEC_BRINU110	110	100	10-16	1,400
ELEC_BRINU125	125	100	10-16	1,350
ELEC_BRINU140	140	125	10-16	1,800
ELEC_BRINU160	160	150	10-16	2,400
ELEC_BRINU180	180	150	10-16	2,250
ELEC_BRINU200	200	200	16	3,450
ELEC_BRINU225	225	200	16	3,100
ELEC_BRINU250	250	250	10	5,100
ELEC_BRINU250-16	250	250	16	5,100
ELEC_BRINU280	280	250	10	4,800
ELEC_BRINU315	315	300	10	7,150
ELEC_BRINU315-16	315	300	16	7,150
ELEC_BRINU355	355	350	10	11,500
ELEC_BRINU400	400	400	10	14,700
ELEC_BRINU400-16	400	400	16	14,700
ELEC_BRINU500	500	450	10	



Bride nue en aluminium (I-52E)

Référence	Ø ext poly	DN	PN	Poids kg
ELEC_BRIALNU25	25	20	10-16	0,213
ELEC_BRIALNU32	32	25	10-16	0,253
ELEC_BRIALNU40	40	32	10-16	0,495
ELEC_BRIALNU50	50	40	10-16	0,570
ELEC_BRIALNU63	63	50	10-16	0,480
ELEC_BRIALNU75	75	65	10-16	0,670
ELEC_BRIALNU90	90	80	10-16	0,740
ELEC_BRIALNU110	110	100	10-16	0,840
ELEC_BRIALNU125	125	100	10-16	0,840
ELEC_BRIALNU140	140	125	10-16	1,080
ELEC_BRIALNU160	160	150	10-16	1,400
ELEC_BRIALNU180	180	150	10-16	1,400
ELEC_BRIALNU200	200	200	10-16	2,240
ELEC_BRIALNU225	225	200	10-16	2,400
ELEC_BRIALNU250	250	250	10	3,000
ELEC_BRIALNU250-16	250	250	16	3,000
ELEC_BRIALNU280	280	250	10	2,800
ELEC_BRIALNU280-16	280	250	16	2,800
ELEC_BRIALNU315	315	300	10	3,600
ELEC_BRIALNU315-16	315	300	16	3,600
ELEC_BRIALNU355	355	350	10	4,800
ELEC_BRIALNU400	400	400	10	6,400

Collet bride anti-fluage complet (I-53E)
Composition : 1 collet, 1 bride anti-fluage
et 1 kit de boulonnerie



Référence	DN	Ø ext poly	Poids kg
ELEC_COLLET25	20	25	0,156
ELEC_COLLET32	25	32	0,225
ELEC_COLLET40	32-40	40	1,400
ELEC_COLLET50	40-50	50	1,520
ELEC_COLLET63	50-60-65	63	1,610
ELEC_COLLET75	60-65-80	75	2,970
ELEC_COLLET90	80	90	3,060
ELEC_COLLET110	100	110	3,355
ELEC_COLLET125	100	125	3,550
ELEC_COLLET140	125	140	6,900
ELEC_COLLET160	150	160	9,870
ELEC_COLLET180	150	180	9,950
ELEC_COLLET200	200	200	15,270
ELEC_COLLET225	200	225	15,350
ELEC_COLLET250	250	250	26,970
ELEC_COLLET280	250	280	26,795
ELEC_COLLET315	300	315	31,410
ELEC_COLLET355	350	355	33,000
ELEC_COLLET400	400	400	51,300

(autres dimensions, nous consulter)