

SELLE DE DÉRIVATION (électrosoudable)



Référence	Ø conduite x Ø PE	Poids kg
ELEC_SD040X020	40 X 20	0,195
ELEC_SD050X020	50 X 20	0,210
ELEC_SD063X020	63 X 20	0,225
ELEC_SD075X020	75 X 20	0,335
ELEC_SD090X020	90 X 20	0,450
ELEC_SD110X020	110 X 20	0,450
ELEC_SD125X020	125 X 20	0,460
ELEC_SD140X020	140 X 20	0,450
ELEC_SD160X020	160 X 20	0,455
ELEC_SD180X020	180 X 20	0,470
ELEC_SD200X020	200 X 20	0,480
ELEC_SD225X020	225 X 20	0,485
ELEC_SD250X020	250 X 20	0,470
ELEC_SD280X020	280 X 20	0,485
ELEC_SD315X020	315 X 20	0,515

Référence	Ø conduite x Ø PE	Poids kg
ELEC_SD040X032	40 X 32	0,265
ELEC_SD050X032	50 X 32	0,295
ELEC_SD063X032	63 X 32	0,235
ELEC_SD075X032	75 X 32	0,250
ELEC_SD090X032	90 X 32	0,285
ELEC_SD110X032	110 X 32	0,445
ELEC_SD125X032	125 X 32	0,460
ELEC_SD140X032	140 X 32	0,460
ELEC_SD160X032	160 X 32	0,460
ELEC_SD180X032	180 X 32	0,465
ELEC_SD200X032	200 X 32	0,470
ELEC_SD225X032	225 X 32	0,450
ELEC_SD250X032	250 X 32	0,485
ELEC_SD280X032	280 X 32	0,500
ELEC_SD315X032	315 X 32	0,495

Référence	Ø conduite x Ø PE	Poids kg
ELEC_SD063X050	63 X 50	0,300
ELEC_SD075X050	75 X 50	0,485
ELEC_SD090X050	90 X 50	0,485
ELEC_SD110X050	110 X 50	0,490
ELEC_SD125X050	125 X 50	0,485
ELEC_SD140X050	140 X 50	0,495
ELEC_SD160X050	160 X 50	0,560
ELEC_SD180X050	180 X 50	0,495
ELEC_SD200X050	200 X 50	0,500
ELEC_SD225X050	225 X 50	0,535
ELEC_SD250X050	250 X 50	0,510
ELEC_SD280X050	280 X 50	0,520
ELEC_SD315X050	315 X 50	0,525

Référence	Ø conduite x Ø PE	Poids kg
ELEC_SD040X025	40 X 25	0,265
ELEC_SD050X025	50 X 25	0,285
ELEC_SD063X025	63 X 25	0,235
ELEC_SD075X025	75 X 25	0,245
ELEC_SD090X025	90 X 25	0,445
ELEC_SD110X025	110 X 25	0,445
ELEC_SD125X025	125 X 25	0,455
ELEC_SD140X025	140 X 25	0,460
ELEC_SD160X025	160 X 25	0,455
ELEC_SD180X025	180 X 25	0,460
ELEC_SD200X025	200 X 25	0,485
ELEC_SD225X025	225 X 25	0,490
ELEC_SD250X025	250 X 25	0,495
ELEC_SD280X025	280 X 25	0,505
ELEC_SD315X025	315 X 25	0,485

Référence	Ø conduite x Ø PE	Poids kg
ELEC_SD040X040	40 X 40	0,280
ELEC_SD050X040	50 X 40	0,295
ELEC_SD063X040	63 X 40	0,240
ELEC_SD075X040	75 X 40	0,340
ELEC_SD090X040	90 X 40	0,470
ELEC_SD110X040	110 X 40	0,470
ELEC_SD125X040	125 X 40	0,485
ELEC_SD140X040	140 X 40	0,475
ELEC_SD160X040	160 X 40	0,480
ELEC_SD180X040	180 X 40	0,500
ELEC_SD200X040	200 X 40	0,485
ELEC_SD225X040	225 X 40	0,485
ELEC_SD250X040	250 X 40	0,495
ELEC_SD280X040	280 X 40	0,525
ELEC_SD315X040	315 X 40	0,510

Référence	Ø conduite x Ø PE	Poids kg
ELEC_SD063X063	63 X 63	0,345
ELEC_SD075X063	75 X 63	0,530
ELEC_SD090X063	90 X 63	0,410
ELEC_SD110X063	110 X 63	0,440
ELEC_SD125X063	125 X 63	0,465
ELEC_SD140X063	140 X 63	0,535
ELEC_SD160X063	160 X 63	0,535
ELEC_SD180X063	180 X 63	0,540
ELEC_SD200X063	200 X 63	0,535
ELEC_SD225X063	225 X 63	0,535
ELEC_SD250X063	250 X 63	0,545
ELEC_SD280X063	280 X 63	0,550
ELEC_SD315X063	315 X 63	0,575

Fiche technique
du catalogue disponible
sur scop-fml.com

16
bars



SELLE DE DÉRIVATION (F-61E) (électrosoudable)



Référence	Ø conduite x Ø PE	Poids kg
ELEC_SD110X075	110 X 75	0,945
ELEC_SD125X075	125 X 75	0,935
ELEC_SD140X075	140 X 75	0,955
ELEC_SD160X075	160 X 75	0,945
ELEC_SD180X075	180 X 75	0,955
ELEC_SD200X075	200 X 75	0,960

Référence	Ø conduite x Ø PE	Poids kg
ELEC_SD090X090	90 X 90	1,070
ELEC_SD110X090	110 X 90	0,990
ELEC_SD125X090	125 X 90	1,025
ELEC_SD140X090	140 X 90	0,940
ELEC_SD160X090	160 X 90	1,015
ELEC_SD180X090	180 X 90	1,025
ELEC_SD200X090	200 X 90	1,020
ELEC_SD225X090	225 X 90	1,540
ELEC_SD250X090	250 X 90	1,525
ELEC_SD280X090	280 X 90	1,500
ELEC_SD315X090	315 X 90	1,535

Référence	Ø conduite x Ø PE	Poids kg
ELEC_SD110X110	110 X 110	1,240
ELEC_SD125X110	125 X 110	1,380
ELEC_SD160X110	160 X 110	1,465
ELEC_SD180X110	180 X 110	1,475
ELEC_SD200X110	200 X 110	1,440
ELEC_SD225X110	225 X 110	1,700
ELEC_SD250X110	250 X 110	1,730
ELEC_SD280X110	280 X 110	1,720
ELEC_SD315X110	315 X 110	1,690

Référence	Ø conduite x Ø PE	Poids kg
ELEC_SD125X125	125 X 125	1,500
ELEC_SD160X125	160 X 125	1,665
ELEC_SD180X125	180 X 125	1,635
ELEC_SD200X125	200 X 125	1,690
ELEC_SD225X125	225 X 125	1,800
ELEC_SD250X125	250 X 125	1,850
ELEC_SD280X125	280 X 125	1,880
ELEC_SD315X125	315 X 125	1,835

SELLE DE RÉPARATION (F-62E)



Référence	Ø conduite	Poids kg
ELEC_SR075	75	0,680
ELEC_SR090	90	0,700
ELEC_SR110	110	0,720
ELEC_SR125	125	0,720
ELEC_SR140	140	0,720
ELEC_SR160	160	0,740
ELEC_SR180	180	0,740
ELEC_SR200	200	0,740
ELEC_SR225	225	0,740
ELEC_SR250	250	0,740
ELEC_SR280	280	0,780
ELEC_SR315	315	0,875
ELEC_SR355	355	0,990
ELEC_SR400	400	1,185
ELEC_SR450	450	1,330
ELEC_SR500	500	1,480
ELEC_SR560	560	1,660
ELEC_SR630	630	1,865
ELEC_SR710	710	2,100
ELEC_SR800	800	2,370
ELEC_SR900	900	2,665
ELEC_SR1000	1000	2,960